

BACnet is a registered trademark of ASHRAE. ASHRAE does not endorse, approve or test products for compliance with ASHRAE standards. Compliance of listed products to the requirements of ASHRAE Standard 135 is the responsibility of BACnet International (BI). BTL is a registered trademark of BI.

BACnet Testing Laboratories Product Listing

This product has been tested at a qualified BACnet Testing Laboratory and found to comply with all the necessary interoperability requirements in place on the published test date. This listing represents the tested capability of the Listed Product. For information on additional functionality that was not covered in the test process, refer to the Manufacturer's PICS statement on the BI website.

Listing Information

Vendor		Listing Status
ExactLogic 5600 Queens Ave NE Suite 500 Otsego, MN 55330 USA		Listed Product
Test Requirements	BACnet Protocol Revision	Date Tested
Requirements as of July 2009	Revision 4 (135-2004)	January 2011

EXL01610, EXL01620, EXL01621, EXL01622, EXL01623, EXL01624,	Product Name	Model Number(s)	Software Version
EXL Digital Display Controller EXL01625, EXL01630, EXL01640, EXL01650, EXL01651, EXL01660, EXL01670, EXL01680, EXL01690, EXL01710, EXL01720		EXL01610, EXL01620, EXL01621, EXL01622, EXL01623, EXL01624, EXL01625, EXL01630, EXL01631, EXL01640, EXL01650, EXL01651, EXL01660, EXL01670, EXL01680, EXL01690,	

Device Profiles

Profile	Model Numbers	
BACnet Application Specific Controller (B-ASC)	All models	

BIBBs Supported

Data Sharing	ReadProperty-B	DS-RP-B
	WriteProperty-B	DS-WP-B
	ReadPropertyMultiple-B	DS-RPM-B
	WritePropertyMultiple-B	DS-WPM-B

	Dynamic Device Binding-B	DM-DDB-B
	Dynamic Object Binding-B	DM-DOB-B
Device and Network	DeviceCommunicationControl-B	DM-DCC-B
Management	Time Synchronization-B	DM-TS-B
	Backup & Restore-B	DM-BR-B
	ReinitializeDevice-B	DM-RD-B

Object Type Support

Analog Input	Analog Output	Analog Value
Binary Input	Binary Output	Binary Value
Device	File	Program

Data Link Layer Options

Media	Options	
MS/TP master	9600, 19200, 38400, 76800	

Character Set Support

ANSI X3.4			