

BACnet is a registered trademark of ASHRAE. ASHRAE does not endorse, approve or test products for compliance with ASHRAE standards. Compliance of listed products to the requirements of ASHRAE Standard 135 is the responsibility of BACnet International (BI). BTL is a registered trademark of BI.

# BACnet Testing Laboratories Product Listing

This product has been tested at a qualified BACnet Testing Laboratory and found to comply with all the necessary interoperability requirements in place on the published test date. This listing represents the tested capability of the Listed Products. For information on additional functionality that was not covered in the test process, refer to the manufacturer's PICS statement on the BI website.

#### **Listing Information (BTL-30109)**

Vendor		Listing Status
Titan Products Ltd. 15 Latham Close Bredbury Park Industrial Estate Bredbury Stockport SK6 2SD United Kingdom		Listed Product
Test Requirements	BACnet Protocol Revision	Date Tested
Requirements as of October 2016 Revision 14 (135-2012)		March, 2017

Product Name	Model Numbers	Software Version
FCU-4 Fan Coil Controller	FCU-402, FCU-403, FCU-404	2.14

#### **Device Profiles**

Profile	Model Numbers
BACnet Application Specific Controller (B-ASC)	All models

### **BIBBs Supported**

Data Sharing	ReadProperty-B	DS-RP-B
	ReadPropertyMultiple-B	DS-RPM-B
	WriteProperty-B	DS-WP-B
	WritePropertyMultiple-B	DS-WPM-B
	COV-B	DS-COV-B

Alarm and Event Notification	Notification Internal-B	AE-N-I-B
	ACK-B	AE-ACK-B
	Information-B	AE-INFO-B

Device Management —	Dynamic Device Binding-A	DM-DDB-A
	Dynamic Device Binding-B	DM-DDB-B

Dynamic Object Binding-B	DM-DOB-B
DeviceCommunicationControl-B	DM-DCC-B
TimeSynchronization-B	DM-TS-B
ReinitializeDevice-B	DM-RD-B
Backup and Restore-B	DM-BR-B

## **Object Type Support**

Analog Input	Analog Output	Analog Value
Binary Input	Binary Output	Binary Value
Device	File	Multi-State Output
Multi-State Value	Notification Class	

# **Data Link Layer Options**

Media	Options
MS/TP Master	9600, 19200, 38400, 76800

### **Character Set Support**

LITE			
UIF-8			
011 0			