

BACnet is a registered trademark of ASHRAE. ASHRAE does not endorse, approve or test products for compliance with ASHRAE standards. Compliance of listed products to the requirements of ASHRAE Standard 135 is the responsibility of BACnet International (BI). BTL is a registered trademark of BI.

BACnet Testing Laboratories Product Listing

This product has been tested at a qualified BACnet Testing Laboratory and found to comply with all the necessary interoperability requirements in place on the published test date. This listing represents the tested capability of the Listed Product. For information on additional functionality that was not covered in the test process, refer to the Manufacturer's PICS statement on the BI website.

Listing Information (BTL-24392)

Vendor		Listing Status
Automated Logic 1150 Roberts Boulevard Kennesaw, GA 30144 USA		Listed Product
Test Requirements BACnet Protocol Revision		Date Tested
Requirements as of November 2014 Revision 9		April 2016

Product Name	Model Numbers	Software Version
Automated Logic AMR Automated Logic AAR	AMR AAR	6.00a-078

Device Profiles

Profile	Model Numbers	
BACnet Application Specific Controller (B-ASC)	All models	

BIBBs Supported

	ReadProperty-B	DS-RP-B
	ReadPropertyMultiple-B	DS-RPM-B
Data Sharing	WriteProperty-B	DS-WP-B
	WritePropertyMultiple-B	DS-WPM-B
	COV-B	DS-COV-B

	Notification Internal-B	AE-N-I-B
Alerman and Event	ACK-B	AE-ACK-B
Alarm and Event Notification	Alarm Summary-B	AE-ASUM-B
	Enrollment Summary-B	AE-ESUM-B
	Information-B	AE-INFO-B

-	Dynamic Device Binding-A	DM-DDB-A
	Dynamic Device Binding-B	DM-DDB-B
	Dynamic Object Binding-B	DM-DOB-B
	DeviceCommunicationControl-B	DM-DCC-B
Device and Network	TimeSynchronization-B	DM-TS-B
Management	UTCTimeSynchronization-B	DM-UTC-B
	ReinitializeDevice-B	DM-RD-B
	List Manipulation-B	DM-LM-B
	Restart-B	DM-R-B

Object Type Support

Binary Value	Calendar	Device
File	Notification Class	

Data Link Layer Options

Media	Options
ARCNET	156 Kbaud
MS/TP Master	9600, 19200, 38400, 76800

Networking Options

Networking Functionality	Media	
Router	MS/TP-to-ARCNET 156 Kbaud	

Character Set Support

ISO 10646 (UTF-8)			