

BACnet is a registered trademark of ASHRAE. ASHRAE does not endorse, approve or test products for compliance with ASHRAE standards. Compliance of listed products to the requirements of ASHRAE Standard 135 is the responsibility of BACnet International. BTL is a registered trademark of BACnet International.

BACnet Testing Laboratories Product Listing

BACnet functionality in each Listed product has been successfully tested at a Recognized BACnet Testing Organization utilizing the industry standard BTL test suite and test policies that were current at the time it was tested. For Listings with multiple products, some products may have less functionality than is indicated by the Listing document. The PICS document provides information on the specific functionality of each product. Note that PICS documents on the BTL Listings site are provided by the manufacturer and are not independently verified by BTL.

Listing Information (BTL-31153)

| Vendor | | Listing Status |
|--|--------------------------|----------------|
| Automated Logic Corporation 1150 Roberts Blvd. Kennesaw, GA 30144 USA | | Listed Product |
| Test Requirements | BACnet Protocol Revision | Date Tested |
| Requirements as of February 2021 | Revision 15 | December 2022 |

| Product Name | Model Numbers | Firmware version |
|---------------------------------|---------------|------------------|
| OptiFlex Compact Segment Router | OFCSR-E2 | 107.07.9035 |

Device Profiles

| Profile | Model Numbers |
|---|---------------|
| BACnet Building Controller (B-BC) | |
| BACnet Router (B-RTR) | All models |
| BACnet Broadcast Management Device (B-BBMD) | |

BIBBs Supported

| | ReadProperty-A | DS-RP-A |
|--------------|-------------------------|----------|
| | ReadProperty-B | DS-RP-B |
| | ReadPropertyMultiple-A | DS-RPM-A |
| | ReadPropertyMultiple-B | DS-RPM-B |
| Data Sharing | WriteProperty-A | DS-WP-A |
| Data Sharing | WriteProperty-B | DS-WP-B |
| | WritePropertyMultiple-A | DS-WPM-A |
| | WritePropertyMultiple-B | DS-WPM-B |
| | Change Of Value-A | DS-COV-A |
| | Change Of Value-B | DS-COV-B |

| | Notification Internal-B | AE-N-I-B |
|-----------------|--------------------------------|-----------|
| | Acknowledge-B | AE-ACK-B |
| Alarm and Event | Alarm Summary-B | AE-ASUM-B |
| Notification | Enrollment Summary-B | AE-ESUM-B |
| | Information-B | AE-INFO-B |
| | Configurable Recipient Lists-B | AE-CRL-B |

| Sebaduling | Internal-B | SCHED-I-B |
|------------|------------|-----------|
| Scheduling | External-B | SCHED-E-B |

| Tranding | Viewing and Modifying Trends Internal-B | T-VMT-I-B |
|----------|---|-----------|
| Trending | Automated Trend Retrieval-B | T-ATR-B |
| | | |
| | Dynamic Device Binding-A | DM-DDB-A |
| | Dynamic Device Binding-B | DM-DDB-B |
| | Dynamic Object Binding-A | DM-DOB-A |
| | Dynamic Object Binding-B | DM-DOB-B |
| | DeviceCommunicationControl-B | DM-DCC-B |
| | TimeSynchronization-A | DM-TS-A |

| | DeviceCommunicationControl-D | DIVI-DCC-B |
|-------------------|----------------------------------|------------|
| | TimeSynchronization-A | DM-TS-A |
| | TimeSynchronization-B | DM-TS-B |
| Device Management | UTCTimeSynchronization-A | DM-UTC-A |
| | UTCTimeSynchronization-B | DM-UTC-B |
| | ReinitializeDevice-B | DM-RD-B |
| | Backup and Restore-B | DM-BR-B |
| | Restart-B | DM-R-B |
| | List Manipulation-B | DM-LM-B |
| | Automatic Time Synchronization-A | DM-ATS-A |
| | Router Configuration-B | NM-RC-B |
| | BBMD Configuration-B | NM-BBMDC-B |

Object Type Support

| Analog Input | Analog Output | Analog Value |
|--------------|-------------------|--------------------|
| Binary Input | Binary Output | Binary Value |
| Calendar | Device | File |
| Loop | Multi-State Value | Notification Class |
| Program | Schedule | Trend Log |

Data Link Layer Options

| Media | Options |
|---------------------|----------------------------|
| | BBMD |
| BACnet/IP (Annex J) | Register as Foreign Device |
| | BACnet/IP, 'DIX' Ethernet |
| MS/TP Master | 9600, 19200, 38400, 76800 |
| Ethernet | ISO 8802-3, 10BASET |
| ARCNET | ARCNET, twisted pair bus |

Character Set Support

| ISO 10646 (UTF-8) | |
|-------------------|--|
| | |
| | |