

BACnet is a registered trademark of ASHRAE. ASHRAE does not endorse, approve or test products for compliance with ASHRAE standards. Compliance of listed products to the requirements of ASHRAE Standard 135 is the responsibility of BACnet International (BI). BTL is a registered trademark of BI.

BACnet Testing Laboratories Product Listing

This product has been tested at a qualified BACnet Testing Laboratory and found to comply with all the necessary interoperability requirements in place on the published test date. This listing represents the tested capability of the Listed Products. For information on additional functionality that was not covered in the test process, refer to the manufacturer's PICS statement on the BI website.

Listing Information (BTL-30159)

Vendor		Listing Status
BELIMO Automation AG Brunnenbacherstr. 1 8340 Hinwil Switzerland		Listed Product
Test Requirements	BACnet Protocol Revision	Date Tested
Requirements as of November 2014	Revision 12 (135-2010)	April 2017

Product Name	Model Numbers	Software Version
	EV0x ¹ R+BAC	
	where x ¹ is 15, 20, 25, 32, 40, 50	
	EV050R+BAC-N	
	Px ² Wx ³ EV-BAC	
	where x^2 is 6065, 6080, 6100, 6125, 6150, 6065, 6080, 6100, 6125	
	where x ³ is 800,1100, 2000, 3100, 4500, 806, 1106, 2006, 3106	
Energy Valve (Europe/Asia)	x⁴R24AX-EV+EV0x ⁵ R	3.01-0000
	where x^4 is L, N, or S where x^5 is 15, 20, 25, 32, 40, 50	
	SR24AX-V+EV050R-N	
	<i>x</i> ⁶ R24AX-EV+P6 <i>x</i> ⁷ W <i>x</i> ⁸ 00EV	
	where x ⁶ is S or G	
	where x^7 is 065, 080, 100, 125, 150	
	where x ⁸ is 8, 11, 20, 31, 45	

| x⁹R24AX-EV+EV0x¹⁰ | RV | where x⁹1 is L, N or S | where x¹⁰ is 15, 20, 25, 32, 40, 50 | x¹¹R24AX- EV+P6x¹²WVx¹³00EV | where x¹¹ is S or G | where x¹² is 065, 080, 100, 125, 150 | where x¹³ is 8, 11, 20, 31, 45 | SRK24AX-EV+EV0 x¹⁴R | where x¹⁴ is 15, 20, 25, 32, 40, 50 | SRK24AX-EV+EV 050R-N | SRK24AX-EV+EV | O50R-N

Device Profiles

Profile	Model Numbers	
BACnet Application Specific Controller (B-ASC)	All models	

BIBBs Supported

Data Sharing	ReadProperty-B	DS-RP-B
	ReadPropertyMultiple-B	DS-RPM-B
	WriteProperty-B	DS-WP-B
	COV-B	DS-COV-B

Device Management	Dynamic Device Binding-B	DM-DDB-B
	Dynamic Object Binding-B	DM-DOB-B
	DeviceCommunicationControl-B	DM-DCC-B

Object Type Support

Analog Input	Analog Output	Analog Value
Binary Input	Binary Value	Device
Multi-State Input	Multi-State Output	Multi-State Value

Data Link Layer Options

Media	Options
BACnet/IP (Annex J)	Register as Foreign Device
MS/TP Master	9600, 19200, 38400, 76800, 115200

Character Set Support

UTF-8		