

BACnet is a registered trademark of ASHRAE. ASHRAE does not endorse, approve or test products for compliance with ASHRAE standards. Compliance of listed products to the requirements of ASHRAE Standard 135 is the responsibility of BACnet International. BTL is a registered trademark of BACnet International.

# **BACnet Testing Laboratories Product Listing**

BACnet functionality in each Listed product has been successfully tested at a Recognized BACnet Testing Organization utilizing the industry standard BTL test suite and test policies that were current at the time it was tested. For Listings with multiple products, some products may have less functionality than is indicated by the Listing document. The PICS document provides information on the specific functionality of each product. Note that PICS documents on the BTL Listings site are provided by the manufacturer and are not independently verified by BTL.

#### **Listing Information (BTL-31379)**

Vendor		Listing Status
Bticino Via Manara, 4 22036 Erba (CO) Italy		Listed Product
Test Requirements	BACnet Protocol Revision	Date Tested
Requirements as of December 2024	Revision 26	July 2025

Product Name	Model Numbers	Firmware version	
UXOne	BT-465001, BT-465002, BT-465003, BT-465004, BT-465005, BT-465006, BT-465007, BT-465008, BT-465080, BT-465081, BT-465082, BT-465083, LG-048900, LG-048901, LG-048902, LG-048903, LG-048907, LG-048905, LG-048981, LG-048982, LG-048983, LG-048923, LG-048924, LG-048925, LG-048927, LG-048928, LG-048929, LG-048930, BT-465015, BT-465023, BT-465024, BT-465029, BT-465030	2.0.76	

#### **Device Profiles**

Profile	Model Numbers
BACnet Application Specific Controller (B-ASC) BACnet Gateway (B-GW)	All models

### **BIBBs Supported**

Data Sharing	ReadProperty-B	DS-RP-B
	WriteProperty-B	DS-WP-B

Device Management	Dynamic Device Binding-B	DM-DDB-B
	Dynamic Object Binding-B	DM-DOB-B
	DeviceCommunicationControl-B	DM-DCC-B
	ReinitializeDevice-B	DM-RD-B
	Foreign Device Registration-A	NM-FDR-A
	Embedded Objects-B	GW-EO-B

### **Object Type Support**

Analog Input	Analog Value	Binary Input
Binary Value	Device	Multi-State Input
Multi-State Value	Network Port	

## **Data Link Layer Options**

Media	Options
BACnet/IP (Annex J)	Register as Foreign Device BACnet/IP, 'DIX' Ethernet

### **Character Set Support**

ICO 40646 (LITE 0)		
I ISO 10646 (UTF-8)		
100 100 10 (011 0)		