

BACnet is a registered trademark of ASHRAE. ASHRAE does not endorse, approve or test products for compliance with ASHRAE standards. Compliance of listed products to the requirements of ASHRAE Standard 135 is the responsibility of BACnet International. BTL is a registered trademark of BACnet International.

BACnet Testing Laboratories Product Listing

BACnet functionality in each Listed product has been successfully tested at a Recognized BACnet Testing Organization utilizing the industry standard BTL test suite and test policies that were current at the time it was tested. For Listings with multiple products, some products may have less functionality than is indicated by the Listing document. The PICS document provides information on the specific functionality of each product. Note that PICS documents on the BTL Listings site are provided by the manufacturer and are not independently verified by BTL.

Listing Information (BTL-30718)

Vendor		Listing Status
Carel S.p.A. Via dell'Industria 11 35020 Brugine, Padova Italy		Listed Product
Test Requirements	Date Tested	
Requirements as of January 2020 Revision 14 (135-2012)		February 2021

duct Name Model Numbers		Firmware version	
	P+5 XX ¹ X ² X ³ X ⁴ X ⁵ X ⁶ X ⁷ X ⁸ X ⁹	4.8.001	
c.pCO Family	where XX ¹ is 00, 04, 0N, K0, HV, W0, A0, PX, DN, AD, BB, DK or EP X ² is S X ³ is B, E, F, M, N, S, T. U or V X ⁴ is A, B, C, D, E, F, G, H, Z, 7, 8 or 9 X ⁵ is 0, 1, 2, 3, 4, 5, 6, A, B, C, D, E, F or Z X ⁶ is 0, 1, 2, 3, 4, 5, 6, 7 or 8 X ⁷ is 0 or E X ⁸ is X, S, M, L, C, Z or J X ⁹ is 0, 1, 2 or K		
	P+D XX ¹ X ² X ³ X ⁴ X ⁵ X ⁶ X ⁷ X ⁸ X ⁹ , P+P XX ¹ X ² X ³ X ⁴ X ⁵ X ⁶ X ⁷ X ⁸ X ⁹ ,	4.8.001	
c.pCO Family	P+R XX ¹ X ² X ³ X ⁴ X ⁵ X ⁶ X ⁷ X ⁸ X ⁹		
	where XX^{1} is 00, 0N, BB, DK, SV, W0, A0, 0R, 0B, HV or NM X^{2} is 0 X^{3} is U, N, B or F X^{4} is C, B, E or H X^{5} is 0, 1, A, B, C, D, E, F, G or H X^{6} is 0 or D		

X ⁷ is 0, E, B, L or F
X ⁸ is F or S
X ⁹ is 0, 1, 2 or K

Device Profiles

Profile	Model Numbers	
BACnet Advanced Application Controller (B-AAC)	All models	

BIBBs Supported

	ReadProperty-B	DS-RP-B		
	ReadPropertyMultiple-B	DS-RPM-B		
	WriteProperty-B	DS-WP-B		
Data Sharing	WritePropertyMultiple-B	DS-WPM-B		
	Change Of Value-B	DS-COV-B		
	Change Of Value Property-B	DS-COVP-B		
	Change Of Value Unsubscribed-B	DS-COVU-B		
	Notification Internal-B	AE-N-I-B		
	Acknowledge-B	AE-ACK-B		
Alarm and Event	Alarm Summary-B	AE-ASUM-B		
Notification	Enrollment Summary-B	AE-ESUM-B		
		AL LOOM D		

Scheduling	Internal-B	SCHED-I-B
	External-B	SCHED-E-B

Information-B

AE-INFO-B

Trending	Viewing and Modifying Trends Internal-B	T-VMT-I-B
	Automated Trend Retrieval-B	T-ATR-B

_	Dynamic Device Binding-A	DM-DDB-A
	Dynamic Device Binding-B	DM-DDB-B
	Dynamic Object Binding-B	DM-DOB-B
	DeviceCommunicationControl-B	DM-DCC-B
Device Management	TimeSynchronization-B	DM-TS-B
	UTCTimeSynchronization-B	DM-UTC-B
	ReinitializeDevice-B	DM-RD-B
	Backup and Restore-B	DM-BR-B
	Restart-B	DM-R-B

Object Type Support

Analog Input	Analog Output	Analog Value
Binary Input	Binary Output	Binary Value
Calendar	Characterstring Value	Device
File	Integer Value	Multi-State Input
Multi-State Output	Multi-State Value	Notification Class
Positive Integer Value	Schedule	Trend Log

Data Link Layer Options

Media	Options		
BACnet/IP (Annex J)	Register as Foreign Device		
DACHEWIF (Annex J)	BACnet/IP, 'DIX' Ethernet		
MS/TP Master	9600, 19200, 38400, 57600, 76800, 115200		

Character Set Support

ISO 10646 (UTE-8)		