

BACnet is a registered trademark of ASHRAE. ASHRAE does not endorse, approve or test products for compliance with ASHRAE standards. Compliance of listed products to the requirements of ASHRAE Standard 135 is the responsibility of BACnet International. BTL is a registered trademark of BACnet International.

BACnet Testing LaboratoriesProduct Listing

BACnet functionality in each Listed product has been successfully tested at a Recognized BACnet Testing Organization utilizing the industry standard BTL test suite and test policies that were current at the time it was tested. For Listings with multiple products, some products may have less functionality than is indicated by the Listing document. The PICS document provides information on the specific functionality of each product. Note that PICS documents on the BTL Listings site are provided by the manufacturer and are not independently verified by BTL.

Listing Information (BTL-30804)

Vendor		Listing Status
Control Solutions, Inc. 10550 South Avenue Chisago City, MN 55013 USA		Listed Product
Test Requirements	BACnet Protocol Revision	Date Tested
Requirements as of February 2021 Revision 15		September 2021

Product Name	Model Numbers	Firmware version
Babel Buster	BB3-7302-V2C, BB3-7302-V3	3.16.7

Device Profiles

Profile	Model Numbers
BACnet Application Specific Controller (B-ASC)	
BACnet Gateway (B-GW)	All models
BACnet Router (B-RTR)	

BIBBs Supported

	ReadProperty-A	DS-RP-A
	ReadProperty-B	DS-RP-B
	ReadPropertyMultiple-B	DS-RPM-B
Data Charina	WriteProperty-A	DS-WP-A
Data Sharing	WriteProperty-B	DS-WP-B
	WritePropertyMultiple-B	DS-WPM-B
	Change Of Value-B	DS-COV-B
	Change Of Value Unsubscribed-B	DS-COVU-B

	Dimensia Davina Diadina A	DM DDD A
Device Management	Dynamic Device Binding-A	DM-DDB-A
	Dynamic Device Binding-B	DM-DDB-B
	Dynamic Object Binding-B	DM-DOB-B
	DeviceCommunicationControl-B	DM-DCC-B
	ReinitializeDevice-B	DM-RD-B
	Restart-B	DM-R-B
	Slave Proxy-B	DM-SP-B
	Router Configuration-B	NM-RC-B
	BBMD Configuration-B	NM-BBMDC-B
	Foreign Device Registration-A	NM-FDR-A
	Embedded Objects-B	GW-EO-B

Object Type Support

Analog Input	Analog Output	Analog Value
Binary Input	Binary Output	Binary Value
Device	Multi-State Input	Multi-State Output
Multi-State Value		

Data Link Layer Options

Media	Options	
DACnot/ID (Annoy I)	BBMD	
BACnet/IP (Annex J)	BACnet/IP, 'DIX' Ethernet	
MS/TP Master	9600, 19200, 38400, 76800	

Character Set Support

ISO 10646	(UTF-8)		