

BACnet is a registered trademark of ASHRAE. ASHRAE does not endorse, approve or test products for compliance with ASHRAE standards. Compliance of listed products to the requirements of ASHRAE Standard 135 is the responsibility of BACnet International. BTL is a registered trademark of BACnet International.

# **BACnet Testing Laboratories**Product Listing

This product has been tested at a qualified BACnet Testing Laboratory and found to comply with all the necessary interoperability requirements in place on the published test date. This listing represents the tested capability of the Listed Products. For information on additional functionality that was not covered in the test process, refer to the Manufacturer's PICS statement on the BACnet International website.

#### **Listing Information (BTL-30546)**

| Vendor   |                          | Listing Status |
|--|--------------------------|----------------|
| Fidelix Oy<br>Martinkyläntie 41<br>01720 Vantaa<br>Finland |                          | Listed Product |
| Test Requirements  | BACnet Protocol Revision | Date Tested    |
| Requirements as of November 2014                           | Revision 14 (135-2012)   | March 2017     |

| Product Name                    | Model Numbers   | Version |
|---------------------------------|---|---------|
| Fidelix PLC Building Controller | FX-2030A,<br>FX-2030A-BASIC,<br>FX-3000-C,<br>FX-SPIDER,<br>FX-SPIDER-40/10 | 12.21   |

#### **Device Profiles**

| Profile                           | Model Numbers |  |
|-----------------------------------|---------------|--|
| BACnet Building Controller (B-BC) | All models    |  |

### **BIBBs Supported**

| Data Sharing | ReadProperty-A          | DS-RP-A  |
|--------------|-------------------------|----------|
|              | ReadProperty-B          | DS-RP-B  |
|              | ReadPropertyMultiple-A  | DS-RPM-A |
|              | ReadPropertyMultiple-B  | DS-RPM-B |
|              | WriteProperty-A         | DS-WP-A  |
|              | WriteProperty-B         | DS-WP-B  |
|              | WritePropertyMultiple-B | DS-WPM-B |

|                   | Notification Internal-B                 | AE-N-I-B  |
|-------------------|---|-----------|
| Alarm and Event   | ACK-B                                   | AE-ACK-B  |
| Notification      | Enrollment Summary-B                    | AE-ESUM-B |
|                   | Information-B                           | AE-INFO-B |
|                   |   |           |
| Cabadulina        | Internal-B                              | SCHED-I-B |
| Scheduling        | External-B                              | SCHED-E-B |
|                   |   |           |
| Tranding          | Viewing and Modifying Trends Internal-B | T-VMT-I-B |
| rrending          | Trending Automated Trend Retrieval-B    |           |
|                   |   |           |
|                   | Dynamic Device Binding-A                | DM-DDB-A  |
|                   | Dynamic Device Binding-B                | DM-DDB-B  |
|                   | Dynamic Object Binding-B                |           |
| Davisa Managament | DeviceCommunicationControl-B            |           |
| Device Management | TimeSynchronization-B                   | DM-TS-B   |
|                   | UTCTimeSynchronization-B                | DM-UTC-B  |
|                   | ReinitializeDevice-B                    | DM-RD-B   |
|                   | Backup and Restore-B                    | DM-BR-B   |

## **Object Type Support**

| Analog Input       | Analog Output      | Analog Value      |
|--------------------|--------------------|-------------------|
| Calendar           | Device             | File              |
| Multi-State Input  | Multi-State Output | Multi-State Value |
| Notification Class | Schedule           | Trend Log         |

## **Data Link Layer Options**

| Media               | Options                           |
|---------------------|-----------------------------------|
| MS/TP Master        | 9600, 19200, 38400, 57600, 115200 |
| BACnet/IP (Annex J) | BACnet/IP, 'DIX' Ethernet         |

## **Character Set Support**

| ISO 10646 (LITE-8) |  |  |
|--------------------|--|--|
| ISO 10646 (UTF-8)  |  |  |