

BACnet is a registered trademark of ASHRAE. ASHRAE does not endorse, approve or test products for compliance with ASHRAE standards. Compliance of listed products to the requirements of ASHRAE Standard 135 is the responsibility of BACnet International. BTL is a registered trademark of BACnet International.

BACnet Testing Laboratories Product Listing

This product has been tested at a qualified BACnet Testing Laboratory and found to comply with all the necessary interoperability requirements in place on the published test date. This listing represents the tested capability of the Listed Products. For information on additional functionality that was not covered in the test process, refer to the Manufacturer's PICS statement on the BACnet International website.

Listing Information (BTL-30416-1)

| Vendor | | Listing Status |
|---|--------------------------|----------------|
| Honeywell 158, Nanhai Road, TEDA Tianjin China | | Listed Product |
| Test Requirements | BACnet Protocol Revision | Date Tested |
| Requirements as of May 2018 | Revision 15 | April 2019 |

| Product Name | Model Numbers | Firmware version |
|--------------------------|---------------|--|
| PUC Series for BACnet IP | PUC8445 | Firmware Revision: 10.06 (build 1) Application Software Version: 10.04 (build 1) |

Device Profiles

| Profile | Model Numbers | |
|--|---------------|--|
| BACnet Application Specific Controller (B-ASC) | All models | |

BIBBs Supported

| Data Sharing | ReadProperty-A | DS-RP-A |
|--------------|-------------------------|----------|
| | ReadProperty-B | DS-RP-B |
| | ReadPropertyMultiple-B | DS-RPM-B |
| | WriteProperty-A | DS-WP-A |
| | WriteProperty-B | DS-WP-B |
| | WritePropertyMultiple-B | DS-WPM-B |
| | Change Of Value-B | DS-COV-B |

| Device Management | Dynamic Device Binding-A | DM-DDB-A |
|-------------------|------------------------------|----------|
| | Dynamic Device Binding-B | DM-DDB-B |
| | Dynamic Object Binding-B | DM-DOB-B |
| | DeviceCommunicationControl-B | DM-DCC-B |
| | TimeSynchronization-B | DM-TS-B |
| | UTCTimeSynchronization-B | DM-UTC-B |
| | ReinitializeDevice-B | DM-RD-B |

Object Type Support

| Analog Input | Analog Output | Analog Value |
|--------------|---------------|-------------------|
| Binary Input | Binary Output | Binary Value |
| Device | File | Multi-State Value |
| Program | | |

Data Link Layer Options

| Media | Options |
|---------------------|----------------------------|
| BACnet/IP (Annex J) | Register as Foreign Device |

Character Set Support

| ISO 10646 (UTF-8) | | |
|-------------------|--|--|