

BACnet is a registered trademark of ASHRAE. ASHRAE does not endorse, approve or test products for compliance with ASHRAE standards. Compliance of listed products to the requirements of ASHRAE Standard 135 is the responsibility of BACnet International. BTL is a registered trademark of BACnet International.

BACnet Testing Laboratories Product Listing

BACnet functionality in each Listed product has been successfully tested at a Recognized BACnet Testing Organization utilizing the industry standard BTL test suite and test policies that were current at the time it was tested. For Listings with multiple products, some products may have less functionality than is indicated by the Listing document. The PICS document provides information on the specific functionality of each product. Note that PICS documents on the BTL Listings site are provided by the manufacturer and are not independently verified by BTL.

Listing Information (BTL-30682)

Vendor		Listing Status
Intesis (HMS Industrial Networks, SLU) Milà i Fontanals, 7 Igualada, Barcelona 08700 Spain		Listed Product
Test Requirements	BACnet Protocol Revision	Date Tested
Requirements as of November 2014 Revision 14 (135-2012)		January 2018

Product Name	Model Numbers	Firmware version
	DALI to	FR: 14.1.0.0
	BACnet IP & MSTP	AS: 1.1.2.0
	KNX to	FR: 14.1.0.0
	BACnet IP & MSTP	AS: 1.0.5.0
	Modbus to	FR: 14.1.0.0
	BACnet IP & MSTP	AS: 1.0.10.0
	M-BUS to	FR: 14.1.0.0
	BACnet IP & MSTP	AS: 1.0.7.0
Intesis BACnet Server Series	Panasonic VRF Systems to	FR: 14.1.0.0
	BACnet IP & MSTP	AS: 1.0.2.0
	Hisense VRF Systems to	FR: 14.1.0.0
	BACnet IP & MSTP	AS: 1.0.1.0
	Hitachi VRF Systems to	FR: 14.1.0.0
	BACnet IP & MSTP	AS: 1.0.1.0
	Samsung NASA VRF Systems to	FR: 14.1.0.0
	BACnet IP & MSTP	AS: 1.0.9.0
	Profinet to	FR: 14.1.0.0
	BACnet IP & MSTP	AS: 1.0.0.0
	Midea VRF Systems to	FR: 14.1.0.0
	BACnet IP & MSTP	AS: 1.0.0.0
		FR: 14.1.0.0
	DALI to BACnet IP	AS: 1.0.3.0
	Modbus to BACnet IP	FR: 14.1.0.0
		AS: 1.0.1.0

AS. 1.0.0.0

Device Profiles

Profile	Model Numbers
BACnet Advanced Application Controller (B-AAC)	All models

BIBBs Supported

Data Sharing	ReadProperty-B	DS-RP-B
	ReadPropertyMultiple-B	DS-RPM-B
	WriteProperty-B	DS-WP-B
	WritePropertyMultiple-B	DS-WPM-B
	COV-B	DS-COV-B
	Notification Internal-B	AE-N-I-B
Alarm and Event	ACK-B	AE-ACK-B
Notification	Alarm Summary-B	AE-ASUM-B
	Information-B	AE-INFO-B
_		-
Scheduling	Scheduling Internal-B	
Trending	Viewing and Modifying Trends Internal-B	T-VMT-I-B
Trending	Viewing and Modifying Multiple Values Internal-B	T-VMMV-I-B
_		-
Device Management	Dynamic Device Binding-A	DM-DDB-A
	Dynamic Device Binding-B	DM-DDB-B
	Dynamic Object Binding-B	DM-DOB-B
	DeviceCommunicationControl-B	DM-DCC-B
	TimeSynchronization-B	DM-TS-B
	ReinitializeDevice-B	DM-RD-B

Object Type Support

Analog Input	Analog Output Analog Value	
Binary Input	Binary Output Binary Value	
Calendar	Device	Multi-State Input
Multi-State Output	Multi-State Value	Notification Class
Schedule	Trend Log	Trend Log Multiple

Data Link Layer Options

Media	Options
BACnet/IP (Annex J)	Register as Foreign Device
	BACnet/IP, 'DIX' Ethernet
MS/TP Master	9600, 19200, 38400, 57600, 76800, 115200

Character Set Support

ISO 10646 (UTE-8)		