

BACnet is a registered trademark of ASHRAE. ASHRAE does not endorse, approve or test products for compliance with ASHRAE standards. Compliance of listed products to the requirements of ASHRAE Standard 135 is the responsibility of BACnet International (BI). BTL is a registered trademark of BI.

# **BACnet Testing Laboratories**Product Listing

This product has been tested at a qualified BACnet Testing Laboratory and found to comply with all the necessary interoperability requirements in place on the published test date. This listing represents the tested capability of the Listed Products. For information on additional functionality that was not covered in the test process, refer to the manufacturer's PICS statement on the BI website.

#### **Listing Information (BTL-30544)**

Vendor		Listing Status
Kieback & Peter Tempelhofer Weg 50 12347 Berlin Germany		Listed Product
Test Requirements	BACnet Protocol Revision	Date Tested
Requirements as of November 2014	Revision 12 (135-2010)	February 2017

Product Name	Model Numbers	Software Version
Automation Advanced Application Controllers	DDC-ME521, DDC-ME521E, RCN-ME901, RCN-ME901E, RCN-ME911, DDC-ME401C, DDC-ME401E, DDC-ME401E, DDC-ME411, DDC-ME411C, DDC-ME411C,	R1.1.0.0

#### **Device Profiles**

Profile	Model Numbers
BACnet Advanced Application Controller (B-AAC)	All models

## **BIBBs Supported**

	ReadProperty-A	DS-RP-A
	ReadProperty-B	DS-RP-B
	ReadPropertyMultiple-A	DS-RPM-A
	ReadPropertyMultiple-B	DS-RPM-B
Data Sharing	WriteProperty-A	DS-WP-A
	WriteProperty-B	DS-WP-B
	WritePropertyMultiple-A	DS-WPM-A
	WritePropertyMultiple-B	DS-WPM-B
	COV-B	DS-COV-B
	Notification Internal-B	AE-N-I-B
Alarm and Event	ACK-B	AE-ACK-B
Notification	Alarm Summary-B	AE-ASUM-B
Notification	Enrollment Summary-B	AE-ESUM-B
	Information-B	AE-INFO-B
Scheduling	Internal-B	SCHED-I-B
	Viewing and Modifying Trends Internal-B	T-VMT-I-B
<u> </u>	Automated Trend Retrieval-B	T-ATR-B
Trending	Viewie e ood Madifiis e Multiple Value aletered D	
	viewing and Modifying Multiple values Internal-B	T-VMMV-I-B
	Viewing and Modifying Multiple Values Internal-B  Automated Multiple Value Retrieval-B	T-VMMV-I-B T-AMVR-B
	Automated Multiple Value Retrieval-B	
	Automated Multiple Value Retrieval-B	
		T-AMVR-B
	Automated Multiple Value Retrieval-B  Dynamic Device Binding-A	T-AMVR-B DM-DDB-A
	Automated Multiple Value Retrieval-B  Dynamic Device Binding-A  Dynamic Device Binding-B	T-AMVR-B  DM-DDB-A  DM-DDB-B
Doving Managarant	Automated Multiple Value Retrieval-B  Dynamic Device Binding-A  Dynamic Device Binding-B  Dynamic Object Binding-A	DM-DDB-A DM-DDB-B DM-DOB-A
Device Management	Automated Multiple Value Retrieval-B  Dynamic Device Binding-A  Dynamic Device Binding-B  Dynamic Object Binding-A  Dynamic Object Binding-B	DM-DDB-A DM-DDB-B DM-DOB-A DM-DOB-A
Device Management	Automated Multiple Value Retrieval-B  Dynamic Device Binding-A  Dynamic Device Binding-B  Dynamic Object Binding-A  Dynamic Object Binding-B  DeviceCommunicationControl-B  TimeSynchronization-B	DM-DDB-A DM-DDB-B DM-DOB-A DM-DOB-B DM-DOB-B
Device Management	Automated Multiple Value Retrieval-B  Dynamic Device Binding-A  Dynamic Device Binding-B  Dynamic Object Binding-A  Dynamic Object Binding-B  DeviceCommunicationControl-B	DM-DDB-A DM-DDB-B DM-DOB-A DM-DOB-B DM-DOC-B DM-TS-B
Device Management	Dynamic Device Binding-A Dynamic Device Binding-B Dynamic Object Binding-A Dynamic Object Binding-B Dynamic Object Binding-B DeviceCommunicationControl-B TimeSynchronization-B UTCTimeSynchronization-B	DM-DDB-A DM-DDB-B DM-DOB-A DM-DOB-B DM-DCC-B DM-TS-B DM-UTC-B

## **Object Type Support**

Accumulator	Analog Input	Analog Output
Analog Value	Binary Input	Binary Output
Binary Value	Calendar	Device
Event Enrollment	File	Loop
Multi-State Value	Notification Class	Program
Schedule	Trend Log	Trend Log Multiple

### **Data Link Layer Options**

Media	Options
BACnet/IP (Annex J)	Register as Foreign Device 1)
MS/TP Master	9600, 19200, 38400, 57600, 115200 <sup>2)</sup>

<sup>1)</sup> supported by product models with suffix "CE"

### **Character Set Support**

ISO 10646(UTF-8) ISO 10646 (UCS-2) Micrososft Double-Byte Character Set (DBCS)

<sup>2)</sup> supported by product models with suffix "C" or no suffix