

BACnet is a registered trademark of ASHRAE. ASHRAE does not endorse, approve or test products for compliance with ASHRAE standards. Compliance of listed products to the requirements of ASHRAE Standard 135 is the responsibility of BACnet International. BTL is a registered trademark of BACnet International.

# **BACnet Testing Laboratories**Product Listing

BACnet functionality in each Listed product has been successfully tested at a Recognized BACnet Testing Organization utilizing the industry standard BTL test suite and test policies that were current at the time it was tested. For Listings with multiple products, some products may have less functionality than is indicated by the Listing document. The PICS document provides information on the specific functionality of each product. Note that PICS documents on the BTL Listings site are provided by the manufacturer and are not independently verified by BTL.

#### **Listing Information (BTL-30824-1)**

Vendor		Listing Status
LOYTEC electronics GmbH Blumengasse 35 1170 Wien Austria		Listed Product
Test Requirements	BACnet Protocol Revision	Date Tested
Requirements as of February 2021	Revision 16	December 2021

Product Name	Model Numbers	Firmware version
BACnet Building Controller		
L-INX Automation Server	LINX-150, LINX-151, LINX-153, LINX-154, LINX-202, LINX-203, LINX-212, LINX-213, LINX-215, LINX-220, LINX-221	7.6
L-GATE Universal Gateway	LGATE-902, LGATE-950, LGATE-951, LGATE-952	7.6
L-ROC Room Controller	LROC-100, LROC-101, LROC-102, LROC-400, LROC-401, LROC-402	7.6
L-DALI Lightning Control	LDALI-PLC2, LDALI-PLC4, LDALI-ME201-U, LDALI-ME204-U	7.6
L-IP Router	LIP-ME201C, LIP-ME202C, LIP-ME204, LIP-ME204C	7.6

#### **Device Profiles**

Profile	Model Numbers
BACnet Building Controller (B-BC)	All models

#### **BIBBs Supported**

	ReadProperty-A	DS-RP-A
	ReadProperty-B	DS-RP-B
	ReadPropertyMultiple-A	DS-RPM-A
	ReadPropertyMultiple-B	DS-RPM-B
	WriteProperty-A	DS-WP-A
Data Sharing	WriteProperty-B	DS-WP-B
Data Sharing	WritePropertyMultiple-B	DS-WPM-B
	Change Of Value-A	DS-COV-A
	Change Of Value-B	DS-COV-B
	Change Of Value Property-A	DS-COVP-A
	Change Of Value Property-B	DS-COVP-B
	Change Of Value Unsubscribed-B	DS-COVU-B
	Notification Internal-B	AE-N-I-B
	Notification External-B	AE-N-E-B
Alama and E	Acknowledge-B	AE-ACK-B
Alarm and Event	Alarm Summary-B	AE-ASUM-B
Notification	Enrollment Summary-B	AE-ESUM-B
	Information-B	AE-INFO-B
	Configurable Recipient Lists-B	AE-CRL-B
·	·	<u>'</u>
	Internal-B	SCHED-I-B
Scheduling	External-B	SCHED-E-B
<u> </u>		
	Viewing and Modifying Trends Internal-B	T-VMT-I-B
Trending	Viewing and Modifying Trends Internal B  Viewing and Modifying Trends External-B	T-VMT-E-B
Tronding	Automated Trend Retrieval-B	T-ATR-B
	Automated Frond Retrieval B	
	Dynamic Device Binding-A	DM-DDB-A
	Dynamic Device Binding-A  Dynamic Device Binding-B	DM-DDB-B
	Dynamic Object Binding-B	DM-DDB-B
	DeviceCommunicationControl-B	DM-DCC-B
	TimeSynchronization-A	DM-TS-A
	TimeSynchronization-B	DM-TS-B
	UTCTimeSynchronization-A	DM-UTC-A
	UTCTimeSynchronization-B	DM-UTC-B
	ReinitializeDevice-B	DM-RD-B
	Backup and Restore-B	DM-RD-B
Device Management	Restart-A	DM-R-A
	Restart-B	DM-R-B
	List Manipulation-B	DM-LM-B
	Object Creation and Deletion-B	DM-OCD-B
	Automatic Time Synchronization-A	DM-OCD-B
-	<b>:</b>	DM-SP-B
-	Slave Proxy-B Connection Establishment-A	NM-CE-A
-		
	BBMD Configuration-B	NM-BBMDC-B
	Foreign Device Registration-A	NM-FDR-A
	Embedded Objects-B	GW-EO-B

### **Object Type Support**

Accumulator	Analog Input	Analog Output	
Analog Value	Binary Input Binary Output		
Binary Value	Calendar	Characterstring Value	
Device	Event Enrollment	File	
Integer Value	Large Analog Value	Loop	
Multi-State Input	Multi-State Output	Multi-State Value	
Notification Class	Octetstring Value	Octetstring Value Positive Integer Value	
Pulse Converter	Schedule	Trend Log	

## **Data Link Layer Options**

Media	Options
	BBMD
BACnet/IP (Annex J)	Register as Foreign Device
, ,	BACnet/IP, 'DIX' Ethernet
MS/TP Master	9600, 19200, 38400, 76800, 115200

#### **Character Set Support**

ISO 8859-1		
ISO 10646 (UCS-2)		
ISO 10646 (UTF-8)		