

BACnet is a registered trademark of ASHRAE. ASHRAE does not endorse, approve or test products for compliance with ASHRAE standards. Compliance of listed products to the requirements of ASHRAE Standard 135 is the responsibility of BACnet International. BTL is a registered trademark of BACnet International.

BACnet Testing Laboratories Product Listing

This product has been tested at a qualified BACnet Testing Laboratory and found to comply with all the necessary interoperability requirements in place on the published test date. This listing represents the tested capability of the Listed Products. For information on additional functionality that was not covered in the test process, refer to the Manufacturer's PICS statement on the BACnet International website.

Listing Information (BTL-30470)

| Vendor | | Listing Status |
|--|--------------------------|----------------|
| Matrix iControl Sdn. Bhd. No. 10, Jalan DBP Dolomite Business Park 68100 Batu Caves Selangor Malaysia | | Listed Product |
| Test Requirements | BACnet Protocol Revision | Date Tested |
| Requirements as of October 2016 | Revision 14 (135-2012) | August 2018 |

| Product Name | Model Numbers | Firmware version |
|-----------------------|---|------------------|
| RCA Series Controller | RCA0664BV, RCA0660BV, RCA0624BV, RCA0620BV, RCA0210BL | 1.14.02.5 |

Device Profiles

| Profile | Model Numbers |
|--|---------------|
| BACnet Application Specific Controller (B-ASC) | All models |

BIBBs Supported

| ReadProperty-B | DS-RP-B |
|-------------------------|--|
| ReadPropertyMultiple-B | DS-RPM-B |
| WriteProperty-B | DS-WP-B |
| WritePropertyMultiple-B | DS-WPM-B |
| Change Of Value-B | DS-COV-B |
| | ReadPropertyMultiple-B WriteProperty-B WritePropertyMultiple-B |

| Scheduling | Weekly Schedule Internal-B | SCHED-WS-I-B |
|------------|----------------------------|---------------|
| eeneddinig | | 001120 1101 5 |

| | Dynamic Device Binding-B | DM-DDB-B |
|-------------------|------------------------------|----------|
| | Dynamic Object Binding-B | DM-DOB-B |
| Device Management | DeviceCommunicationControl-B | DM-DCC-B |
| _ | TimeSynchronization-B | DM-TS-B |
| | ReinitializeDevice-B | DM-RD-B |

Object Type Support

| Analog Input | Analog Output | Analog Value |
|-----------------|-------------------|------------------------|
| Binary Input | Binary Output | Binary Value |
| Bitstring Value | Device | File |
| Loop | Multi-State Value | Positive Integer Value |
| Schedule | | |

Data Link Layer Options

| Media | Options |
|--------------|-----------------------------------|
| MS/TP Master | 9600, 19200, 38400, 76800, 115200 |

Character Set Support

ISO 10646 (UTF-8)